FS-6950DN

A3 MONOCHROME WORKGROUP PRINTER

SPACE TO THINK


BIGGER.

For workgroups that require a wide variety of output up to A3, at speed. This flexible new generation printer, with up to 1,000 sheets paper capacity, can accommodate increases in memory, especially helpful for CAD and DTP environments. Low noise, compact design and cost-effective ECOSYS technology give you more space to think about big ideas.

- 32 pages per minute in A4, 16 pages per minute in A3
- 64 MB memory standard, upgradeable to 576 MB
- PDF direct printing from USB Flash Memory devices
- Eco-friendly, ozone-free technology
- Long-life components and easy maintenance
- Duplex unit and network connectivity as standard

Benefit from a rare combination of talents: high quality A3 output yet small footprint and a remarkably low noise level.





Kyocera shape controlled toner makes the most of every one of the 1,200 dots per inch (above: conventional; below: shape controlled toner).







FS-6950DN

A3 MONOCHROME WORKGROUP PRINTER

ECOSYS devices are designed to ECosys. minimise both direct costs and costs, indirect such as administration maintenance. and consumables. The cartridge-free system requires only the toner to be replaced. The modular design concept allows you to add workflow-enhancing functions and a wide variety of paper handling capabilities as required. Integrated system software provides lona-term cross-network compatibility. Kyocera's long-life components cost you and the environment less

System platform:

The FS-6950DN offers USB, parallel and network connectivity as standard and delivers problem-free system administration. Kyocera's single platform technology means that the same driver can be used for every Kyocera PCL/PostScript print device on the network; from single-user desktop printers to high-end multifunctional systems. Only Kyocera offers this effortless combination of IT sophistication and high-performance paper handling expertise.

PRESCRIBE He

With the Kyocera page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (even multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

KM-NET for Client/KM-NET Viewer

The settings of all printers on the network can be checked visually and amended from any Windows[®] PC. KM-NET for Client enables easy setup and monitoring of the printer status via parallel, USB or network connection. KM-NET Viewer is an advanced printer management software tool using the standardized protocol SNMP.

GENERAL

Technology: Kyocera ECOSYS, Laser

Engine speed: Up to 32/16 pages per minute A4/A3 simplex Up to 23/10 pages per minute A4/A3 duplex Resolution: Fine1200, Fast1200, 600x600, 300x300.

Time to first page: 9 seconds or less Warm-up time: 15 seconds or less from power on

Duty cycle: Max. 150,000 pages per month, max. average 20,000 pages per month Power source: AC 220 ~ 240 V, 50/60 Hz Power consumption: Printing: 555 W, Stand-by: 10 W,

Power-Saving (ECOpower): 4.9 W Noise (ISO 7779): Printing: 50 dB(A), Stand-by: 40 dB(A), Power-Saving (ECOpower): Immeasurably Iow

Dimensions (W x D x H): Main unit: 469 x 395 x 285 mm

Weight: Main unit: Approx. 19.5 kg Certifications: TÜV/CS, CE, PTS This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 250-sheet universal paper cassette. Input capacity: 250-sheet universal paper cassette, 60-120 g/m², A3, B4, A4-R, A4, A5, B5, Letter, Letter, Legal, Ledger, Custom (139.7 x 148 mm to 297 x 432 mm) 100-sheet multi-purpose tray, 60-220 g/m², A3, B4, A4-R, A4, A5, A6-R, B5, Letter, Letter-R, Legal, Ledger, Custom (70 x 148 mm to 297 x 450 mm)

Max. input capacity with 4 optional paper feeders PF-430: 1,350 sheets

Duplex as standard supports A3–A5-R, 60-120 g/m² Output capacity: 250 sheets face-down with paper full sensor and optional 250 sheets face-up with PT 430

6-10 Talavera Road North Ryde NSW 2113

Phone: (02) 9888 9999

Fax: (02) 9888-9588

Processor: PowerPC 750 / 400 MHz

Memory: Standard 64 MB + ECOmemory, max, 576 MB Emulations: PCL6/PCL5e incl. PIL, KPDL 3 (PostScript 3 compatible), PDF direct print, Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630, KCGL (HP 7550A) Controller language: PRESCRIBE IIe

Fonts: 80 outline fonts accessible in all emulations, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417, Downloadable fonts: Kyocera, PCL + TrueType format,

Type 1 + 3 format

Print features: Duplex, Accounting, PDF direct printing, eMPS, low noise, no Ozone, USB-Host

INTERFACES

Standard interface: High speed bi-directional parallel (IEEE 1284), USB 2.0 (Hi-Speed), Fast Ethernet 10Base-T/100Base-TX, USB Host Interface dedicated for USB Flash Memory device, KUIO-LV option interface slot

Multiple interface connection (MIC): Allows simultaneous data transfer via up to four interfaces, with each interface having its own virtual printer.

Paper handling

PF-430 Paper feeder (max. 4 units): 250 sheets, 60-120 g/m², A3, B4, A4R, A4, A5, B5, Letter, Letter-R, Legal, Ledger, Custom (139.7 x 148 mm to 297 x 432 mm) PT-430 Paper tray: 250 sheets face-up output tray

Memory Printer memory: 1 DDR SDRAM DIMM slot (64, 128, 256 or 512 MB)

Storage memory: 1 slot for either CompactFlash[®] memory card type 1 (up to 2 GB) for forms, fonts, logos, macro storage or Microdrive[™] (up to 4 GB) for forms, fonts, logos, macro storage as well as document management with eMPS

functions such as quick copy, proof and hold, private print and job storage.

1 USB Host Interface (USB 1.1) for USB Flash Memory device supports PDF direct printing

Optional interface

IB-21E Network card: 10Base-T/100Base-TX IB-11 Serial interface: RS-232C serial interface (max. 115.2 kbps)

CONSUMABLES

TK-440 Toner-kit: Microfine toner for 15,000 pages with 5% coverage (ISO/IEC 19752)

Capacity of starter toner is 7,500 pages with 5% coverage (ISO/IEC 19752)

MK-440 Maintenance Kit: Due for installation at each 300,000 pages

Standard Warranty

2-year onsite warranty as standard.

Kyocera guarantees the drum and developer for 2 years or 300,000 pages (whichever occurs sooner), provided each printer is used, cleaned and maintained in accordance with the service instructions.

Extended Warranty Options

ECO-FS-3003: Optional Upgrade to 3rd year onsite warranty ECO-FS-3004: Optional Upgrade to 4th year onsite warranty

MODEL CONFIGURATIONS

FS-6950DN

FS-6950DTN (FS-6950DN + PF-430)



Your Kyocera Business Partner:

MELBOURNE OFFICE

Cnr Forbes St & Riverside Dr West End QLD 4101 Phone: (07) 3844 6686 Fax: (07) 3844 8569

PERTH OFFICE 104 Walters Drive Osborne Park WA 6017 Phone: (08) 92019155 Fax: (08) 92019511

ADELAIDE OFFICE 53 Rundle Street Kent Town SA 5067 Phone: (08) 7421 2000 Fax: (08) 7421 2001



NEW ZEALAND OFFICE 1-3 Parkhead Place Albany New Zealand Phone: (649) 415 4517 Fax: (649) 415 4597

CANBERRA OFFICE Epicorp Centre 401Clunies Ross Street Acton ACT 2601 Phone: (02) 6229 1729 Fax: (02) 6229 1701

SYDNEY HEAD OFFICE Unit 2, 993 North Road Murrumbeena VIC 3163 Phone: (03) 9579 1555 Eax: (03) 9579 1544

BRISBANE OFFICE